



**40m/80m kit**

- T1 5.0uH secondary, 34T of #30, (18 in.), on T30-2 core (red) primaries 17T each of #30, (2 x 9.5 in.), wound bifilar primary wound on top of secondary
- L1 4.7uH, 33T of #30, (17 in.), on T30-2 core (red)
- T2 primary 6T of #30, (10 in.), on BN-43-2402 core secondaries 3T bifilar of #30, (2 x 4.5 in.)
- RFC1 4 turns #26, (5 in.), on BN-43-2402 core
- T3 secondary 5T of #30, (9 in.), on BN-43-2402 core primaries 4T each of #30, (2 x 6 in.), wound bifilar
- L2 1.4uH, 19T #26, (12 in.), on T37-2 core (red)
- L3 1.4uH, 19T #26, (12 in.), on T37-2 core (red)

Note: Components mounted to the bottom of the board include size 1206 SMT capacitors C50 through C73 and SOICs U1, U2, U3, U5, U6, U7 and U8

|   |         |             |
|---|---------|-------------|
| SoftRock Projects                         |         |             |
| <b>G0BBL-M0PUB-G8BTR 40m/80m RXTXv6.2</b> |         |             |
| Tony KB9YIG                               | 6/12/07 | Page 1 of 2 |